

Geotechnical design for precast piles

A look at the bearing capacity of driven precast concrete piles



Geological section automation

The use of Bentley Solutions's gINT

Underground utility detection

Standardisation for underground service detection

Tunnel pre-drilling

DAT instruments using pre-drilling instruments on Tunnel Boring Machines

GEOTECHNICAL COURSE DATES:
Geotechnical Foundation Design - 20th Jan 2015
Soil Description Workshop
3rd Dec 2014
21st Jan 2015

H&S COURSE DATES:
Avoiding Danger from Underground Services
5th Dec 2014, 30th Jan 2015
Safe Supervision of Geotechnical Sites:
10th - 12th Dec 2014

GEOTECHNICAL COURSE DATES:
Rock Description Workshop
28th Jan 2015, 10th March 2015
In Situ Testing
18th November 2014
Lab Testing
27th Jan 2015

WANT TO ADVERTISE IN THE GEOTECHNICA?

1. Select advert size. (Full Page, Quarter Page, Directory Entry)
2. Select timescale. (1, 3, 6 or 12 Months)
3. Format your artwork. (Adobe PDF, .jpg or .png)
4. Send your artwork to us. (magazine@geotechnica.co.uk, or contact us on 01295 670990)

Standard Rate	Member's Rate	3 Months	6 Months	12 Months
£550	£500	POA	POA	POA
£310	£280	POA	POA	POA
£160	£145	POA	POA	POA
£30	£25	POA	POA	POA

2012 Advertising Rates (€) - All members will benefit from discounted rates.




EQUIPE TRAINING

Health and Safety Courses

DELIVERED IN PARTNERSHIP WITH: **RPA SAFETY SERVICES Ltd**

IOSH Safe Supervision of Geotechnical Sites

This three day geotechnically focussed health and safety course has been developed by industry specialists and is a unique course for managers and supervisors involved in projects in the drilling and geotechnical industry. The course is certified by IOSH and has been approved by The Environment Agency, Thames Water, AGS and BDA and also meets all of the requirements of the UKCG (formerly the Main Contractor's Group).

NEXT COURSE DATES: 10th - 12th December 2014
4th - 6th February 2015

IOSH Avoiding Danger from Underground Services

This one day geotechnically focussed health and safety course follows the requirements and guidance set out within HSG47 and includes the four chapters; identifying and managing the dangers; planning the work; detecting, identifying and marking and safe excavation. Important aspects include the use of real examples from the geotechnical industry and delivery by chartered advisors who are from within the industry.

NEXT COURSE DATES: 5th December 2014
30th January 2015

Safe Working on Geotechnical Sites

This one day geotechnically focussed health and safety course has been developed by industry specialists as a foundation to site safety for all personnel involved in projects in the drilling and geotechnical industry. Its aim is to impart the core safety skills required of those working on geotechnical sites by building on their existing specialist technical skills and making it relevant to their place of work.

NEXT COURSE DATES: Please contact Equipe



For more information, contact Equipe Training:

 info@equipegroup.com
 www.equipegroup.com
 +44 (0)1295 670990
 +44 (0)1295 678232

 Equipe Group
 @EquipeGroup
 EquipeGroup

Contents

- 7 [Geological Section Automation](#)
Writing for theGeotechnica this month is Gary Logan, Director of Sales at Bentley Systems, a global leader dedicated to providing architects, engineers, geospatial professionals, constructors, and owner-operators with comprehensive software solutions for sustaining infrastructure. This month Gary discusses the use of gINT during geological section automation.
- 13 [Underground Utility Detection Standardisation](#)
Writing for theGeotechnica this month is Piers Edgell, Senior Account Manager of Landmark® Information Group, a leading provider of land, property and environmental risk data and digital mapping. Piers looks at the introduction of the new PAS 128 specification that has been introduced to standardise underground utility detection, verification and location and looks at what it means to the industry.
- 19 [Driven Precast Concrete Piles](#)
Writing for theGeotechnica this month is Bob Handley, an Engineer in the Piling Division of Per Aarsleff (UK) Ltd, a subsidiary of Per Aarsleff A/S, one of Denmark's leading civil engineering contractors. In this article Bob reveals more about precast piles which were previously discussed in Issue 29 of theGeotechnica, back in April of this year.
- 23 [Pre-Drilling in Tunnel Works](#)
Our fourth article this month comes from one of our regular contributors in DAT instruments, an Italian company that specialises in the design and production of advanced foundation instruments and software. In this article DAT instruments provide details on pre-drilling in tunnelling works and what equipment is out there to make the process easier.
- 27 [Directory](#)

GEOTECHNICAL COURSES

SOIL DESCRIPTION WORKSHOP - £265 + VAT

3rd December 2014
21st January 2015
25th February 2015

ROCK DESCRIPTION WORKSHOP - £265 + VAT

28th January 2015
10th March 2015

GEOTECHNICAL FOUNDATION DESIGN - £225 + VAT

20th January 2015
26th February 2015

IN SITU TESTING - £225 + VAT

18th November 2014
5th March 2015

GEOTECHNICAL LABORATORY TESTING AWARENESS - £225 + VAT

27th January 2015
26th May 2015

**BOOK ONLINE NOW @
WWW.EQUIPEGROUP.COM**



UPCOMING COURSES IN 2014/15

FROM THE UK'S LEADING GEOTECHNICAL TRAINING PROVIDER

Supported by



Welcome

Welcome to the 35th Edition of **theGeotechnica** - the UK's fastest growing online geotechnically focussed e-magazine.

This month, once again, we have a fantastic line-up of insightful and informative articles that make for a must-read.

The first article of this month's issue comes from Gary Logan, Director of Sales at Bentley Systems, a global leader dedicated to providing architects, engineers, geospatial professionals, constructors, and owner-operators with comprehensive software solutions for sustaining infrastructure. This month Gary discusses the use of gINT during geological section automation.

Writing our second article of this month's issue is Piers Edgell, Senior Account Manager of Landmark® Information Group, a leading provider of land, property and environmental risk data and digital mapping. Piers looks at the introduction of the new PAS 128 specification that has been introduced to standardise underground utility detection, verification and location and looks at what it means to the industry.



The third article comes from Bob Handley, an Engineer in the Piling Division of Per Aarsleff (UK) Ltd, a subsidiary of Per Aarsleff A/S, one of Denmark's leading civil engineering contractors. In this article Bob reveals more about precast piles which were previously discussed in Issue 29 of **theGeotechnica**,

back in April of this year.

Our fourth article this month comes from one of our regular contributors in DAT instruments, an Italian company that specialises in the design and production of advanced foundation instruments and software. In this article DAT instruments provide details on pre-drilling in tunnelling works and what equipment is out there to make the process easier.

As with every new edition of the magazine, the Editorial Team here at **theGeotechnica** will be on the lookout for even more new, original and interesting content from all corners of the sector, and would actively encourage all readers to come forward with any appropriate and relevant content - whether it be a small news item or a detailed case study of works recently completed or being undertaken. If this content is media rich and interactive, then all the better. We are looking to increase the already large readership of the magazine through better social media integration and promotion, as well as improving content month on month.

Finally, for any content that is submitted we will ensure that an advertising space, proportionate to the quality of content provided, is reserved should you wish to place an advert in that single edition of the magazine. We hope you enjoy this month's edition of the magazine and are inspired to contribute your own content for the coming editions of **theGeotechnica**.

Editorial Team,
theGeotechnica

To book your place, please contact Equipe Training:



info@equipegroup.com



www.equipegroup.com



+44 (0)1295 670990



+44 (0)1295 678232

Other courses are available. Please visit our website for more details.

EQUIPE GROUP

GEOLOGICAL SECTION AUTOMATION

Writing for *theGeotechnica* this month is Gary Logan, Director of Sales at [Bentley Systems](#), a global leader dedicated to providing architects, engineers, geospatial professionals, constructors, and owner-operators with comprehensive software solutions for sustaining infrastructure. This month Gary discusses the use of gINT during geological section automation.

Hours Become Seconds


A global provider of professional, technical, and management support services to a broad range of markets, AECOM delivers solutions that create, enhance, and sustain the world's built, natural, and social environments. The Fortune 500 company was engaged by the Carillion/Morgan Sindall Joint Venture (CMSJV) to be the lead designer from feasibility through detailed design of the A1 Dishforth to Leeming Improvement Scheme in North Yorkshire, United Kingdom. The USD 460 million scheme upgraded 22 kilometers of the existing A1 trunk road to a dual three-lane motorway with the aim to improve safety, reduce accidents, and provide extra road capacity for future growth. AECOM chose

gINT, Bentley's geotechnical and geoenvironmental data management and reporting software, to manage and report all geological and geotechnical information. gINT saved up to six months (800-1,000 man-hours) in manual drafting time by enabling AECOM to produce geological sections in seconds rather than hours.

50 Years of Legacy Data

"One of the biggest challenges at the start of the project was finding a way to make use of the huge amount of legacy data."

One of the biggest challenges at the start of the project was



AECOM used gINT to visualize CPT profiles alongside conventional boreholes in cross sections.

finding a way to make use of the huge amount of legacy data. Records from the ad hoc improvements made since the A1's opening included short-length roadway upgrades from single to dual carriageway, and roundabout replacements with grade-separated junctions. These projects included 10 different phases of ground investigations carried out by various contractors over the years. Together the legacy data comprised more than

900 exploratory holes – approximately 400 boreholes and 500 trial pits – along with associated laboratory testing data.

AECOM chose gINT to store and manage this historical data due to the easy and flexible way in which the data could be processed. With gINT software, engineers and geo-professionals can gather, manage, present, and report on subsurface data more

"Most of the historical data for the A1 was available as hard copy only..."

efficiently and with greater accuracy. Most of the historical data for the A1 was available as hard copy only, so a data entry team was employed to create electronic files from the paper records. The electronic records were entered into Excel tables compatible with the AGS

(Association of Geotechnical and Geoenvironmental Specialists) file structure, which is the standard geotechnical exchange format used in many countries, including the U.K., Ireland, and the Middle East. This allowed easy validation and import into gINT.

Having more than 50 years of ground investigation data together in one readily accessible database proved to be invaluable ►►

KeyLogbook®

digital logging solution



BOREHOLE AND TRIAL PIT LOGGING SOLUTION

KeyLogbook® revolutionises the way site data is captured, recorded and transmitted. Drillers and engineers no longer need to keep re-entering the same data repetitively. You will therefore reduce errors and make the whole process **simpler, faster, smarter, greener and more efficient**. The system records all site data at source and transmits it directly from site, saving time and money from the outset.

- Revolutionises the way site data is captured, recorded and transmitted
- **Confidence that all data is complete**
- AGS Data available immediately
- **Accurate financial control**
- Quicker, more efficient turnaround of logs and data
- **Easier to maintain chain of custody**
- NEW TRIAL PIT LOGGING FUNCTION

FULL PACKAGE AVAILABLE FOR PURCHASE NOW
30 DAY FREE TRIAL AVAILABLE FOR DOWNLOAD NOW



SAFER | G





THE WORLD'S FIRST SENSOR BASED ROTARY RIG GUARD

Introducing Equipe Geosolutions' latest product innovation: SAFER G. Primarily aimed at land based rotary drilling rigs, SAFER G is a sensor-based guarding system that allows for increased access and productivity whilst operating on site, removing the need for restrictive and fully enclosing guarding systems. A less obstructive method of guarding, the sensors operate outdoor in all weathers and function in even the most harsh conditions and environments including: Rain, sleet, snow, ice and associated low temperatures; Sun and associated high temperatures; Dust, dirt (including mud, soil, gravel, vegetation, etc); High volumes of water, air, mist, foam and other flush medium. The sensors are fully encased, with no moving parts and ultra-robust.



THE BENEFITS OF SAFER G

- Improves rig **productivity**
- **Improves reliability** in personnel protection
- **Complies** with safety and machinery legislation
- Fully compatible with **all rig types**
- Creates a **safer work environment**



For more information, contact Equipe Geosolutions:

- ✉ info@equipegroup.com
- 🌐 www.equipegroup.com
- ☎ +44 (0)1295 670990
- 📠 +44 (0)1295 678232

- 🌐 Equipé Group
- 🐦 @EquipeGroup
- 📺 EquipeGroup

For more information, contact Equipe Geosolutions:

- ✉ info@equipegroup.com
- 🌐 www.equipegroup.com
- ☎ +44 (0)1295 670990
- 📠 +44 (0)1295 678232

- 🌐 Equipé Group
- 🐦 @EquipeGroup
- 📺 EquipeGroup



UNDERGROUND UTILITY DETECTION STANDARDISATION

Writing for **theGeotechnica** this month is Piers Edgell, Senior Account Manager of [Landmark@ Information Group](#), a leading provider of land, property and environmental risk data and digital mapping. Piers looks at the introduction of the new PAS 128 specification that has been introduced to standardise underground utility detection, verification and location and looks at what it means to the industry.

During the summer, a new industry standard was launched at the Institution of Civil Engineers that aims to provide a clear and definite provision for those who are engaged in the detection, verification and

location of utilities – whether they are active, dormant or even unknown utility services.

The specification, which the British Standards Institution has termed as 'PAS 128:2014',

aims to not only set clear provisions for those operating in this space but will ultimately lead to more effective planning and far safer execution of ground/civil works, street excavations and utility-based activities.

Most organisations are today fully aware of the risks related to corporate manslaughter, negligence claims or civil damages and therefore

determine potentially hidden or unknown risks, which could make themselves known as a land development or site excavation commences. This is where PAS 128 is set to make a real difference.

With no agreed or published UK standards related to the detection, verification or location of underground services, PAS 128 aims to provide clarity in the service provided and methods employed, as well as offer consistency in the

“It is also a way of safeguarding land professionals from potential risks or ‘unknowns’ that may be hidden under ground.”

approach to data capture. It is also a way of safeguarding land professionals from potential risks or ‘unknowns’ that may be hidden under ground.

PAS 128 is made up of four levels of differing survey types. These have been defined as the following:

- Survey type D - desktop utility records search, whereby utilities are identified through the analysis of paper and digital records or reports, such as those available from Landmark;
- Survey type C - site reconnaissance, where existing records are validated by the visual inspection of physical evidence observed during a site visit;
- Survey type B - detection, where utilities are detected using geophysical techniques; and

“It pays to ensure as much research and due diligence is undertaken at the outset to determine potentially hidden or unknown risks...”

‘forearmed is forewarned’. It pays to ensure as much research and due diligence is undertaken at the outset to

- Survey type A - verification, where underground services are located via a manhole, inspection chamber or through excavation.

“The range of survey types have been designed to take a categorised approach, meaning that differing levels of data may be required for differing projects...”

The range of survey types have been designed to take a categorised approach, meaning that differing levels of data may be required for differing projects, so the Survey type can be selected depending on the confidence levels required. Survey type D requires the least effort in the sense that desktop utility reports can be easily accessed from the office, while at the other end of the scale, survey type A requires full physical investigations at the site to determine whether any utilities are present.

“The way in which the appropriate survey level is selected will be based on a number of factors...”

The way in which the appropriate survey level is selected will be based on a number of factors, such as the density of services within the area in question, and it might well be the case that more than one survey is selected once initial desk-based research draws its conclusions. ►►



“With no formal standardisation previously in place for the detection, verification or location of underground utilities, we fully encourage our customers that operate in the construction, engineering and built environment sectors to contact the BSI to obtain a copy of the PAS 128 standard.”

Here at Landmark, we fully welcome the new PAS 128 specification as it aims to

provide consistent and clear best practice in identifying underground utilities. With no formal standardisation previously in place for the detection, verification or location of underground utilities, we fully encourage our customers that operate in the construction, engineering and built environment sectors to contact the BSI to obtain a copy of the PAS 128 standard.

As well as demonstrating that as much research has been undertaken at the outset from a personnel security point of view, it will also help firms manage risk in other areas of their business. For example, having a clearer understanding of what utility features lie below the surface may help them to avoid implications such as cost of damages should an asset be inadvertently hit. Or, coming

across unknown cabling, pipework, water supplies or other utilities may create delays in a project, which has the potential to incur financial penalties. These are commonly overlooked, yet can reflect negatively on a consultancy's reputation if unforeseen delays occur on a project.

Understanding the features that lie below the surface is therefore crucial before any excavations commence. Detailed Utilities Reports are available that collate all utility information into a single source, providing a clear outline of what is below the surface.

As recommended in Survey type D, this level of due diligence provides valuable information that will help reduce the risk of potential litigation if damage is caused, the project is delayed, or any added danger to the workforce occurs.

The desktop utility search reports from Landmark form the basis of the detection process outlined in PAS 128. By accessing such reports, it demonstrates that reasonable steps have been taken to ensure that as much is known about a site at the outset.

Ultimately, the more comprehensive and reliable information that can be gathered, the better informed everyone is to understand the 'known' risks and minimise the 'unknown' risks to an ALARP level. Data is key and by achieving a PAS compliant survey, you can avoid potential project delays, injuries or service disruption. ■

GEOTECHNICAL DATA MANAGEMENT SOFTWARE

TRANSFORMED

START TRANSFORMING THE WAY YOU VIEW DATA WITH A FREE TRIAL TODAY



info@keynetix.com +44(0) 1527 688 888

QUALITY SLOPE DATA

from our innovative
slope climbing rigs



01452 527743
geotech@geoeng.co.uk
www.geoeng.co.uk





THE GEOTECHNICAL ACADEMY

On-the-ground practical development for geo-professionals

The Geotechnical Academy is a partnership between Geotechnical Engineering Ltd & Equipe Training, providing unique, high quality vocational geotechnical CPD development for early career engineering professionals

Group 8 Enrolling now for Dec 2014

Interested? For further information:

Contact Amanda Thompson on: 01452 527743

amanda.thompson@geoeng.co.uk

Or visit our website: www.geotechnicalacademy.co.uk

◇ peer support ◇ mentoring ◇ debate & discussion ◇ practical sessions ◇ demonstrations ◇ knowledge transfer ◇ confidence building ◇ external lecturers



CPD Approved Courses for Geotechnical Academy Alumni

Specifying Site Investigations

This one day course will look at the various methods available to carry out intrusive and non intrusive investigation. Whilst the course will concentrate on geotechnical methods some geo-environmental methods will be briefly discussed. The course will look at the aims of SI and categorise the various stages in an investigation.

Soil Description Workshop

From 2007 new European Standards have started replacing the British Standards (Codes) under which investigations in the UK have been carried out. UK working practice will have to change to meet these new requirements but few practitioners are aware of the changes or the timetable. The workshop will comprise a series of lectures on the changes, and lectures on soil description followed by practical sessions describing soil samples.

Rock Description Workshop

From 2007 new European Standards have started replacing the British Standards (Codes) under which investigations in the UK have been carried out. UK working practice will have to change to meet these new requirements but few practitioners are aware of the changes or the timetable. The workshop will comprise a series of lectures on the changes, and lectures on rock description followed by practical sessions describing rock and compiling mechanical logs of rock core.

In Situ Testing

The course will cover both the theory and the practice of various In Situ Testing techniques used on typical geotechnical projects. In addition the courses will consider the effect that Eurocodes will have on the UK's current practice. This course provides an overview of in situ tests used in common practice and some of the more specialist tests together with their advantages and limitations.

Instrumentation and Monitoring

The course comprises a comprehensive one day appreciation of the complete process involved in Instrumentation and Monitoring in the geotechnical environment. The course provides an overview of the current guidance documents and their requirements. The course will consider the design of both individual installations and the installation of suites of instruments in the wider site context.

Basic Foundation Awareness

This one day course will provide a general overview of foundation design. It will include an assessment of the use and choice of shallow foundations and piles. It will cover the derivation of bearing capacity formula and their use. Exercises will be carried out to calculate the working loads and settlement of simple foundations. The methods used to calculate these will be in accordance with those described in Eurocode.

IOSH Working Safely on Geotechnical Sites

This one day course is developed by industry specialists within RPA Safety Services and Equipe Training as a foundation to site safety. Its aim is to impart the core safety skills required of those working on geotechnical sites by building on their existing specialist technical skills. After attending the course, candidates should be able to identify hazards on site, understand basic safety legislation, participate fully and confidently in site safety consultation and manage priority risks to a sufficient standard.

IOSH Avoiding Danger from Underground Services

Partnering with RPA Safety Services once again, Equipe provide another IOSH certified health and safety course. This one day course is aimed at anybody involved in specifying, instructing, managing, supervising or actually breaking ground and really addresses the problems and risks related to underground services, which may be encountered during both planning and execution of geotechnical projects.

IOSH Safe Supervision of Geotechnical Sites

Equipe has partnered with RPA Safety Services, an independent occupational health and safety specialist, to provide a unique IOSH certified course for the Drilling and Geotechnics industry. The three day course is certified by IOSH, is specifically focussed on the geotechnical industry and provides a totally unique and relevant Health and Safety course for managers and supervisors.

Visit our websites for more details:
www.geotechnicalacademy.co.uk
www.equipegroup.com



THE
GEOTECHNICAL
ACADEMY

A collaboration between



15% off
Equipe Courses
for Academy
Alumni

DRIVEN PRECAST CONCRETE PILES



Writing for **theGeotechnica** this month is Bob Handley, an Engineer in the Piling Division of [Per Aarsleff \(UK\) Ltd](#), a subsidiary of Per Aarsleff A/S, one of Denmark's leading civil engineering contractors. In this article Bob reveals more about precast piles which were previously discussed in [Issue 29 of theGeotechnica](#), back in April of this year.

“Old British Standards”

Historically the geotechnical design of bearing piles has utilised the concept of a global factor of safety and BS 8004:1986 Code of practice for foundations recommended that this should be in the range 2.0 to 3.0 depending on a

number of considerations:

- Piling technique.
- Quality and quantity of site investigation data.
- Load testing regime.
- Settlement specification

The factor of safety employed in pile design is intended to

safeguard against failure of the pile/soil interaction that provides the resistance to the applied load, and to ensure that pile settlement characteristics are within acceptable limits in the service condition. Typically design for driven precast concrete piles would use a global factor of safety at the lower end of this range in combination with a dynamic load testing regime, for the following reasons:

- The pile is manufactured under quality assured factory

conditions and arrives at the pile location preformed; consequently the risks associated with placing fresh concrete in the ground are absent. The pile can be inspected prior to driving and the successful achievement of the design pile toe level and/or driving resistance can be safely acknowledged as a demonstration of pile shaft integrity on completion.

- Even with relatively basic site investigation data, a reasonable estimate of pile

length can be made. The records of resistance to penetration on probe piles installed in working pile locations can be compared with reported soil conditions. Piles may be installed to a calculated embedment or length, to a dynamic resistance

“In variable soil conditions the precast concrete pile can be driven on until the design resistance to penetration is achieved...”

or set, or to a combination of both. In variable soil conditions the precast concrete pile can be driven on until the design resistance to penetration is achieved, as opposed to say forming a CFA pile without first seeing the spoil that has been excavated.

- “A driven pile is a tested pile”.

“New British Standards”

BS EN 1997-1:2004 Eurocode 7 Geotechnical design General rules and its associated National Annex published in 2007 adopts a different approach using partial factors.

“Eurocode 7 currently allows the designer to adopt one of three design approaches...”

Eurocode 7 currently allows the designer to adopt one of three design approaches to the manner in which the partial factors applied to the actions are combined with the partial material and resistance factors


applied to the pile resistance provided by the soil. The choice of design approach is dictated by the National Annex and for bearing pile design in the UK Design Approach 1 has been adopted. This process requires the pile designer to consider two combinations of factored actions (partial factor sets A1 and A2). For bearing pile design combination 1 generally governs the structural design of the pile whereas combination 2 governs the geotechnical design.

Eurocode 7 allows the designer a number of different ways of deriving characteristic values of pile resistance including the use of static or dynamic load tests on piles, the use of direct ground test results (e.g. cone penetration tests), set measurements and calculation based on soil properties obtained by intrusive ground investigation.

“In the case of load tests, set measurements and direct ground tests correlation factors are applied to the mean and minimum values of resistance...”

In the case of load tests, set measurements and direct ground tests correlation factors are applied to the mean and minimum values of resistance to derive characteristic values and these will vary according to the extent of testing and measurements.

In the UK design by calculation is the norm and Eurocode 7 requires the application of a model factor to the



calculated ultimate resistances to derive characteristic values. A reduction in the model factor from 1.4 to 1.2 is permitted if a preliminary pile is load tested to the calculated ultimate

“The benefits of this will depend on the scope of piling works being large enough to justify the cost of the preliminary static load test.”

resistance. The benefits of this will depend on the scope of piling works being large enough to justify the cost of the preliminary static load test.

Once characteristic values

of resistance have been established the relevant design values can be derived by application of the partial factors applicable to load combinations 1 and 2 (Sets R1 and R4). Lower values of the R4 factors are permitted if a minimum 1% of piles are proof load tested or if settlement can be reliably predicted, or when settlement is of no concern.

Design values of pile resistance are compared with design values of actions (loads) applied to the pile to ensure that a geotechnical (GEO) and structural (STR) ultimate limit state is not exceeded. Verification of serviceability limit states (i.e. settlement or deflection) is normally demonstrated implicitly by the

verification of the ultimate limit state, but may require explicit verification in itself.

A change for the better or the worse?

“The declared purpose of the Structural Eurocodes was to provide a set of unified calculation methods to assess the “mechanical resistance” of structures, provide a basis for specifying contracts for construction work and serve as a framework for harmonising technical specifications.”

The declared purpose of the Structural Eurocodes was to provide a set of unified calculation methods to assess the “mechanical resistance” of structures, provide a basis for specifying contracts for construction work and serve as a framework for harmonising technical specifications. Individual members of the EU would be free to determine certain parameters within their National Annexes to the various standards.

Unfortunately, in the case of bearing piles generally and driven piles in particular, the compounded effect of the Eurocode 7 partial factors has led to an increase in the overall design factor of safety compared to the global factor of safety that has been acceptable under BS 8004.

Safe working load	500kN
BS 8004 FOS	2.0 (dynamic load testing regime applied)
Required ultimate resistance	1000kN

Eurocode factor A2	1.15 (based on 50/50 permanent/variable load)
Model factor	1.4 (without a preliminary load test)
Eurocode factor R4	1.7 (on base resistance without proof load tests)
Required ultimate resistance	1369kN

Consider this example (above) of a driven precast concrete pile which is predominantly end bearing, driven to a set and is effectively self-testing:

The increase in required soil resistance resulting from designing to Eurocode 7 is 37%; this would mean an increase in section size from 250mm square to 300mm square. To restore the BS 8004 status quo would require a preliminary

load test (model factor 1.2) and at least 1% proof load tests (R4 factor 1.5) with a resulting requirement for 1035kN soil resistance. Either option impacts heavily on the sustainable and economical use of driven piles.

Some might question the wisdom of a global factor of safety as low as 2.0 but the reality is that this has been the norm for the driven precast concrete

sector of the UK piling industry for the last 30 years without any evidence that the safety standards of construction have been compromised across the board.

4 The Future

All parts of Eurocode 7 are currently under review by a number of “evolution” (working) groups managed by CEN Committee TC 250/SC7. Fortunately the UK is well represented, holding the Chair of SC7 and with expert representation in EG7 Pile Design and EG8 Harmonisation. There is recognition that the current range of permitted design approaches is too broad and that in the UK driven piling design has been adversely affected by the combination of partial factors.

Watch this space! ■

The First Name in Piling

Specialist ■ Driven ■ Piling ■ Contractors

Do you need:


- Sustainability? ■ A Quality Assured System?
- Swift & Accurate Installation? ■ Experts in Piling?

Offering the Centrum Reinforced Precast Concrete Piling System in sections from 200mm² to 600m², plus steel bearing piles to accommodate high tension loads; Aarsleff have the experience and technical capability to offer all of the above and more.



AARSLEFF

Aarsleff, Hawton Lane,
Balderton, Newark,
Nottinghamshire NG24 3BU
T. 01636 611140
E. info@arsleff.co.uk
www.aarsleff.co.uk



PRE-DRILLING IN TUNNEL WORKS

Our fourth article this month comes from one of our regular contributors in DAT instruments, an Italian company that specialises in the design and production of advanced foundation instruments and software. In this article DAT instruments provide details on pre-drilling in tunnelling works and what equipment is out there to make the process easier.

DAT instruments have designed and launched a product aimed to work in tunnelling projects. The product combines accurate electronic equipment with long performance sensors to face pre-drilling activities, with the purpose of investigating the ground to be dug and the vault of a tunnel when a Tunnel Boring Machine (TBM) is in operation.

Underground works, especially tunnelling works, must consider all soil strata. Continuous monitoring of the geological pattern is required to quickly acquire soil information and deliver the best result on time, not only during the excavation by the TBM but also during the process of soil investigation, above the tunnel vault. Here is where DAT instruments, specialist within the production of drilling and piling electronic monitoring instrumentation, had the opportunity to install a datalogger on a small drill rig, placed on the TBM. The purpose was to pre-drill the soil before

the TBM excavation, allowing a faster and longer daily dig. **“There are two major benefits by using this instrumentation: monitoring soil structure even 70m at the front of the TBM and investigation of soil above the tunnel vault.”**

There are two major benefits by using this instrumentation: monitoring soil even 70m at the front of the TBM and investigation of soil above the tunnel vault.

Thanks to the small drill on which it is installed, the datalogger allows to test and explore the ground in front of the TBM, recording the diagraphy before the dig of the tunnel. In this way the building company perfectly knows the characteristics of ground that



it is going to dig and the best equipment to be used, avoiding choosing cutting tools based on best guesses and increasing the productivity.

At the same time the TBM auxiliary drilling machine can be used to test the vault of the tunnel (that operation usually does not reach 5m of depth) aimed to define the type of soil to be encountered, to choose the best coating to be taken

and to determine the final type of sensors that will monitor the **“Last but not least: the data logger provides an opportunity to certify the work...”**


tunnel during the entire life of the structure. Last but not least: the data logger provides an opportunity to certify the work, allowing you to deliver to

the project manager a detailed description of each dig.

From a technical perspective the datalogger created by DAT instruments for this particular type of processing is the JET 4000 AME / J, equipped with a special set of sensors that allows data transfer through USB pen drive and to process the parameters using the software JET S 104. There are several parameters recorded

by the DAT instruments equipment, including: drill depth, rod feed force, rod feed speed, rotation torque and rotation speed; mast inclination axes X and Y (optional); drilling fluid pressure, date and start/end time of work and duration of work, calculation of relative energy of the ground.

Assistance and worldwide support: Although the dataloggers and sensors ►



Pressure sensors on the TBM.

are highly sophisticated electronic instruments, they are not delicate. All products DAT instruments are made keeping in mind the work site where they will operate, with a large

use of stainless steel and latest generation polymer resins that ensure maximum strength and durability. However, the Italian company has developed a service that leaves no room

for doubts and uncertainty and has as main objective the proximity to the customer and his site problems. As stated by Amedeo Valoroso, owner of DAT instruments: "We have

local distributors all over the world with high-level technical assistance, capable of carrying out any installation and support customers during the use of the instrumentation. Reseller technicians are formed directly by us and are continually supported by Italian experts. They are always ready to intervene in the work site for any client's needs. In fact DAT instruments has always been available to solve problems by phone, e-mail or Skype. However today our service has evolved, with the opportunity to realize video conferencing with operators in the pipeline. It is possible to install and configure the software remotely, in order to make life easier in the work sites. It is also possible to provide education and training."

A successful example - the BBT: Among the many successful applications recorded by DAT instruments in the specific field

"... the intervention in the Brenner Base Tunnel (BBT), appears one of the most significant because of the importance of the work at European level..."

of tunnelling, the intervention in the Brenner Base Tunnel (BBT), appears one of the most significant because of the importance of the work at European level but also for the specific commitment of the Italian company that with his

staff has followed all the stages of the building, installation assistance.

The Italian technicians were involved in the pre-drilling of the service tunnel built transversely to the main rail tunnel linking Italy to Austria. A gallery of 10 kilometers with a width of about 6-7 m. In this site the data logger was installed on a small drill that had the task of testing the waters to about 70 m, anticipating the work of the TBM of 20-25 m

At the same time the drill, rotating 90°, carried out surveys of the entire of the tunnel providing precise diagraphies of the ground ahead of the TBM. ■

Directory

WANT TO ADVERTISE IN THE GEOTECHNICA?

1. Select your advert size.
(Full, Half, Quarter Page, Directory Entry)
2. Select timescale.
(1, 3, 6 or 12 Months)
3. Format your artwork.
(Adobe PDF, .jpg or .png)
4. Send your artwork to us.
(magazine@geotechnica.co.uk,
or contact us on 01295 670990)

Advert Size	Standard Rate	Member's Rate	3 Months	6 Months	12 Months
Full Page	£550	£500	POA	POA	POA
Half Page	£310	£280	POA	POA	POA
Quarter Page	£160	£145	POA	POA	POA
Directory	£30	£25	POA	POA	POA

All adverts placed by Drilling Academy™ members will benefit from discounted rates.

2012 Advertising Rates (£) - All rates are given excluding VAT.

borehole surveying software

[GEOMEM](#)

24 John Huband Drive, Birkhill, Angus, DD2 5RY
United Kingdom
Tel: 01382 329 011 Fax: 01382 230 256
Email: tech@geomem.com

consultants

[GROUND TECHNOLOGY](#)

Ground Technology Services, Maple Road,
Kings Lynn, Norfolk, PE34 3AF
Tel: 01553 817657 Fax: 01553 817658
Email: mail@groundtechnology.co.uk

drilling contractors

[APEX DRILLING SERVICES](#)

Sturmi Way, Bridgend, CF33 6BZ
Tel: 01656 749149
Email: thomas.martin@apex-drilling.com

[BOREHOLE SOLUTION SITE INVESTIGATION](#)

13 Great North Road, Buckden, St Neots,
Cambridgeshire, PE19 5XJ
Tel: 01480 812457 Mob: 07969 715655
Email: boreholesolutions@gmail.com

[CONCEPT](#)

Unit 8 Warple Mews, Warple Way, London
W3 0RF
Tel: 020 8811 2880 Fax: 020 8811 2881
Email: si@conceptconsultants.co.uk

[DYNAMIC SAMPLING UK](#)

Unit 8 Victory Park Way, Victory Road
Derby, DE24 8ZF
Tel: 01332 771104 Mob: 07836 365533
Email: info@dynamicsampling.co.uk

[GEOTECHNICAL ENGINEERING](#)

Centurion House, Olympus Business Park,
Quedgeley, Gloucester, GL2 4NF
Tel: 01452 527743 Fax: 01452 729314
Email: geotech@geoeng.co.uk

[RGI GEOTECHNICAL INVESTIGATION](#)

Unit 37, Longfield Road, Sydenham Industrial
Estate, Leamington Spa, Warwickshire, CV31
1XB
Tel/Fax: 01926 886329 Mob: 07748871546
Email: rgi10@aol.com

drilling suppliers

[DRILLWELL](#)

Unit 3, Rotherham Close, Killamarsh, Sheffield,
S21 2JU
Tel: 0114 248 7833 Fax: 0114 2487997
Email: sales@drillwell.co.uk

field instrumentation

[GEOTECHNICAL OBSERVATIONS](#)

The Peter Vaughan Building, 9 Avro Way,
Brooklands, Weybridge, Surrey KT13 0YF
Tel: 01932 352040 Fax: 01932 356375
Email: info@geo-observations.com

geophysics

[EUROPEAN GEOPHYSICAL SERVICES](#)

22 Sansaw Business Park, Hadnall, Shrewsbury,
Shropshire SY4 4AS
Tel: 01939 210 710 Fax: 01939 210 532
Email: eurogeophys@europeangeophysical.com

[TERRADAT](#)

Unit 1, Link Trade Park, Penarth Road, Cardiff,
CF11 8TQ
Tel: 08707 303050 Fax: 08707 303051
Email: web@terradat.co.uk

geotechnical software

[KEYNETX LTD](#)

Systems Park, Moons Park, Burnt Meadow
Road,
Redditch, Worcestershire, B98 9PA
Tel: 01527 68888 Fax: 01527 62880
Email: sales@keynetix.com

geotechnical specialists

[GEOTECHNICAL ENGINEERING](#)

Centurion House, Olympus Business Park,
Quedgeley, Gloucester, GL2 4NF
Tel: 01452 527743 Fax: 01452 729314
Email: geotech@geoeng.co.uk

[GEOTECHNICAL OBSERVATIONS](#)

The Peter Vaughan Building, 9 Avro Way,
Brooklands, Weybridge, Surrey KT13 0YF
Tel: 01932 352040 Fax: 01932 356375
Email: info@geo-observations.com

[SOILS LIMITED](#)

Newton House, Tadworth
Surrey, KT20 5SR
Tel: 01737 814221 Fax: 01737 812557
Email: southwest@soilslimited.co.uk

Soils Limited
Newton House
Tadworth
Surrey
KT20 5SR

soils
LIMITED
Geotechnical and
Environmental Consultants

Phone 01737 814221
Fax 01737 812557
Web www.soilslimited.co.uk

ground protection

[Ground-Guards™](#)

Rapid-Install Trackways

HIRE or SALE

39kg panels easily installed by hand
Guaranteed unbreakable by vehicles up to 120 tonnes*
* See website

Tel: 0113 267 6000

Email: info@ground-guards.co.uk

Web: www.ground-guards.co.uk

health and safety

[EB SAFETY](#)

Tel: 01926 642465 Mob: 07881858271
Email: ebetts@ebsafety.co.uk

laboratory services

ALCONTROL LABORATORIES

Units 7 & 8 Hawarden Business Park, Manor Road, Hawarden, Deeside, Flintshire CH5 3US
Tel: 01244 528 700 Fax: 01244 528 701
Email: hawarden.sales@alcontrol.com

CHEMTEST

Depot Road, Newmarket, CB8 0AL
Tel: 01638 606 070 Fax: 01638 606 071
Email: peter.noone@chemtest.co.uk

CONCEPT

Unit 8 Warple Mews, Warple Way, London W3 0RF
Tel: 020 8811 2880 Fax: 020 8811 2881
Email: si@conceptconsultants.co.uk

GEOLABS

Bucknalls Lane, Garston, Watford, Hertfordshire, WD25 9XX
Tel: 01923 892 190 Fax: 01923 892 191
Email: admin@geolabs.co.uk

K4 SOILS LABORATORY

Unit 8, Olds Close, Watford, Hertfordshire, WD18 9RU
Tel: 01923 711288 Fax: 01923 711311
Email: office@k4soils.com

site investigation

CONCEPT

Unit 8 Warple Mews, Warple Way, London W3 0RF
Tel: 020 8811 2880 Fax: 020 8811 2881
Email: si@conceptconsultants.co.uk

training and education

EQUIPE GROUP

The Paddocks, Home Farm Offices, The Upton Estate, Banbury, Oxford, OX15 6HU
Tel: 01295 670990 Fax: 01295 678232
Email: info@equipegroup.com


Rotary Drillers

We have vacancies available for experienced Lead Rotary Drillers, both in the UK and Worldwide.

- Excellent Rates of Pay
- Conventional, Wireline and Geothermal positions all available
- Onshore and Offshore
- Minimum 5 Years experience
- and NVQ Level 2 is preferable

All interested applicants, please forward your CV to:

keith.spires@equipegroup.com



casagrande UK

DRILLING AND MINIPILING RIGS



CASAGRANDE UK
UNIT 3, BOTLEY LANE
CHESHAM
BUCKS HP5 1XS
TEL: 01494 794990



theGeotechnica



Driving our industry forward...

Equipe Group
The Paddocks, Home Farm Drive
The Upton Estate
Banbury, OX15 6HU

Find us online:



Equipe Group



@EquipeGroup



Equipe Training Ltd

